



**Nitrogen inflator machine for  
buses, lorries, large and  
medium-sized trucks**

1. Inert gas, less heat expansion,  
lower tire burst risk, higher security
2. Slower aging of wheel rims and  
rubber, longer service life of tire.
3. Larger molecules, slower tire  
leakage rate, less unnecessary wear  
and tear.
4. Greater tire grip performance,  
higher security, more comfort, higher  
efficiency, lower fuel consumption

# TECHNO 388

## Large and medium sized truck tire Nitrogen Machine

Supply with  
**EXTERNAL TANK 300 Ltr**



EXTRA EXTERNAL TANK 300 Lt



built in air compressor booster

Technical Specification >>>

**TECHNO 388**

Power	AC380V/ 50Hz
Nitrogen generating power	30W
Nitrogen Purity	95% -99.5% (Without oxygen content)
Inlet Pressure	0.95 - 1.0 Mpa
Air input	800-1000NL/min (with a large amount of nitrogen and continuous maximum, with small amount of nitrogen choose the minimum vallue)
Air inlet temperature	<80°C
Oil content	10ppm
Nitrogen Gas pressure	0.8 Mpa
Nitrogen gas flow	1000 - 5000/L/H
Turbo Power	2.2KW
Display mode	LED digital display
Operating Temperature	-40°C-+70°C
Air tank Weight	97 Kg
Caze size	1600x 700x 600
Air tank size	620x1750(mm)